



DENSE HIGH ALUMINA BRICKS

ORIMAX - 50	50	1.6	35	22	2.25	350	± 1.0	1480	Special dense low iron alumina bricks for various applications like sponge iron rotary kilns, fertilizers, petrochemicals plants and for EAF Roof.
ORIMAX - I	54	1.5	35	20	2.30	400	± 1.5	1500	
ORIMAX - II	54	1.5	35	22	2.20	400	± 0.5	1520	
ORIMAX - 60	60	1.0	36	18	2.50	500	± 1.0	1550	
ORIMAX - 60A	60	1.0	36	20	2.40	400	± 0.5	1500	
ORIMAX - 70	70	0.8	37	22	2.60	600	± 1.0	1600	
ORIMAX - 70A	70	1.0	37	21	2.45	400	± 0.5	1550	
ORIMAX - 75	75	1.5	37	23	2.60	400	± 0.8	1600	
ORIMAX - 80	80	1.0	38	22	2.60	400	± 0.5	1620	
ORIMAX - 80A	80	1.0	38	20	2.85	500	± 0.5	1550	
ORIMAX - 85A	85	1.5	38	18	2.90	500	± 1.5	1600	
ORISIL - I	58	2.0	36	22	2.40	400	± 1.0	1520	
ORISIL - II (BRO - 62)	60	1.5	36	25	2.30	350	± 1.0	1550	
ORISIL - III (BRN - 62)	62	1.5	36	18	2.50	500	± 0.8	1600	
ORISIL - IV	58	1.5	36	23	2.30	400	± 1.0	1550	
ORIMULL - I	66	1.5	37	15	2.50	800	± 0.5	1550	
ORIMULL - II	72	1.5	38	21	2.50	600	± 0.2	1650	
ORIKOR - 80D	80	0.6	38	17	2.10	800	± 0.3	1650	
ORIKOR - 90	90	0.8	38	18	3.10	1000	± 0.3	1600	
ORIKOR - 90D	90	0.3	40	19	3.20	1000	± 0.2	1700	
ORIKOR - 98	98	0.3	40	21	3.00	800	± 0.2	1600	
KORONDAL - XD	90	0.5	40	18	3.00	600	± 0.2	1700	
ORIMAX - 98	98	0.5	38	21	3.00	850	± 0.3	1650	